
List of tables

Table 1	
Serial data interface cards	4
Table 2	
Power consumption	7
Table 3	
Environmental specifications	7
Table 4	
Connectors J1 and J2 pin assignments	16
Table 5	
SDI paddle board address switch settings	17
Table 6	
SDI paddle board baud rate switch settings	18
Table 7	
SDI paddle board DTE/DCE mode switch settings	18
Table 8	
Serial port configuration parameters	20
Table 9	
Connectors J1, J2, J3, and J4 pin assignments	28
Table 10	
QSDI paddle board baud rate switch settings	29
Table 11	
QSDI paddle board address switch settings	30
Table 12	
QSDI paddle board DTE/DCE mode switch settings	31

Table 13	
QSDI serial port configuration parameters	32
Table 14	
Connector J1 pin assignments	39
Table 15	
Connector J2 pin assignments	40
Table 16	
QSDI card address switch settings	41
Table 17	
QSDI card baud rate switch settings	42
Table 18	
QSDI card DTE/DCE mode switch settings	43
Table 19	
Serial port configuration parameters	45
Table 20	
Characteristics of synchronous ports	53
Table 21	
QPC513 interconnection specifications	55
Table 22	
Connector J1 and J2 pin assignments—RS-232-C interface	57
Table 23	
Connector J1 and J2 pin assignments—high-speed interface	58
Table 24	
ESDI card address switch settings	60
Table 25	
ESDI card DTE/DCE mode jumper settings	62
Table 26	
ESDI card RS-232-C/high-speed interface jumper settings	62
Table 27	
Serial port configuration parameters	63
Table 28	
LAPB frame structure	68

Table 29	
Commands and responses	70

